

Schedule Commands Cheat Sheet

User Commands	PBS/Torque	Slurm	LSF	SGE	Loadleveler
Jobsubmission	qsub [script file]	sbatch [script file]	bsub [script file]	qsub [script file]	llsubmit [script file]
Jobdeletion	qdel uob idl	scancel fiob idl	bkill [job idl]	qdel uob idl	llcancel fjob idl
Jobstatus(b)'job	qstat uob id]	squeue uob id]	bjobs uob id]	qstat -u * [-j job id]	llq -u [username]
Jobstatus(b)' user)	qstat -u [user name]	squeue -u [user name]	bjobs -u [user name]	qstat [-u user name]	llq -u [user name]
Jobhold	qhold uob id]	scontrol hold uob id]	bstop uob id]	qhold uob id]	llhold -r uob id]
Jobrelease	qrls uob id]	scontrol release uob id]	bresume uob id]	qrls uob id]	llhold -r uob id]
Queue list	qstat -Q	squeue	bqueues	qconf -sql	llclass
Node list	pbsnodes -l	sinfo -N OR scontrol show nodes	bhosts	qhost	llstatus -L machine
Clusterstatus	qstat -a	sinfo	bqueues	qhost -q	llstatus -L cluster
GUI	xpbsmon	sview	xlsf OR xlsbatch	qmon	xload
Environment	PBS/Torque	Slurm	LSF	SGE	Loadleveler
Job ID	\$PBS_JOBID	\$SLURM_JOBID	\$LSB_JOBID	\$JOB_ID	\$LOAD_STEP_ID
Submit Directory	\$PBS_O_WORKDIR	\$SLURM_SUBMIT_DIR	\$LSB_SUBCWD	\$SGE_O_WORKDIR	\$LOADL_STEP_INITDIR
Submit Host	\$PBS_O_HOST	\$SLURM_SUBMIT_HOST	\$LSB_SUB_HOST	\$SGE_O_HOST	N/A
Node List	\$PBS_NODEFILE	\$SLURM_JOB_NODELIST	\$LSB_HOSTS/LSB_MCPU_HOST	\$PE_HOSTFILE	\$LOADL_PROCESSOR_LIST
Job Array Index	\$PBS_ARRAYID	\$SLURM_ARRAY_TASK_ID	\$LSB_JOBINDEX	\$SGE_TASK_ID	
Job Specification	PBS/Torque	Slurm	LSF	SGE	Loadleveler
Script directive	#PBS	#SBATCH	#BSUB	#\$	#@
Queue	-q [queue]	-p [queue]	-q [queue]	-q [queue]	class=[queue]
Node Count	-l nodes=[count]	-N [min[-max]]	-n [count]	N/A	node=[count]
CPU count	-l ppn= [count] OR -l mppwidth=[PE count]	-n [count]	-n [count]	-pe [PE] [count]	N/A
Wall Clock Limit	-l walltime=[hh:mm:ss]	-t [min] OR -t [days-hh:mm:ss]	-W [hh:mm:ss]	-l h_rt=[seconds]	wall clock limit=[hh:mm:ss]
Standard Output File	-o [file_name]	-o [file_name]	-o [file_name]	-o [file_name]	output=[file_name]
Standard Error File	-e [file_name]	-e [file_name]	-e [file_name]	-e [file_name]	error=[file_name]
Combine stdout/err	-j oe (both to stdout) OR -j eo (both to stderr)	(use -o without -e)	(use -o without -e)	-j yes	N/A
Copy Environment	-V	--export=[ALL NONE variables]	N/A	-V	Environment=COPY_ALL
Event Notification	-m abe	--mail-type=[events]	-B or -N	-m abe	notification= start error complete never always
Email Address	-M [address]	--mail-user=[address]	-u [address]	-M [address]	Notify_user=[address]
Job Name	-N [name]	--job-name=[name]	-J [name]	-N [name]	job name=[name]
Job Restart	-r [y n]	--requeue OR --no-requeue (NOTE: configurable default)	-r	-r [yes no]	Restart = [yes no]
Working Directory	N/A	--workdir=[dir_name]	(submission directory)	-wd [directory]	initialdir=[directory]
Resource Sharing	-l naccesspolicy=singlejob	--exclusive OR --shared	-x	-l exclusive	node_usage=not_shared
Memory Size	-l mem=[MB]	--mem=[mem][M G T] OR --mem-per-cpu=[mem][M G T]	-M [MB]	-l mem_free=[memory][K M G]	requirements= (Memory >= [MB])
Account to charge	-W group_list=[account]	--account=[account]	-P [account]	-A [account]	n/a
Tasks Per Node	-l mppnppn [PEs_per node]	--tasks-per-node=[count]	N/A	(Fixed allocation_rule in PE)	tasks_per_node=[count]
CPUs Per Task	n/a	--cpus-per-task=[count]	n/a	n/a	n/a
Job Dependency	-d [job_id]	--depend=[state:job_id]	-w [done exit finish]	-hold_jid [job_id job_name]	n/a
Job Project	n/a	--wckey=[name]	-P [name]	- P [name]	n/a
Job host preference	n/a	--nodelist=[nodes]AND/OR --exclude=[nodes]	-m [nodes]	-q[queue]@[node] OR -q [queue]@[hostgroup]	n/a
Quality of Service	-l qos=[name]	--qos=[name]	n/a	n/a	n/a
Job Arrays	-t [array_spec]	--array=[array_spec] (Slurm version 2.6+)	J"name[array_spec]"	-t [array_spec]	n/a
Generic Resources	-l other=[resource_spec]	--gres=[resource_spec]	n/a	-l [resource]=[value]	n/a
Licenses	n/a	--licenses=[license_spec]	-R "rusage[license_spec]"	-l [license]=[count]	n/a
Begin Time	-A "YYYY-MM-DD HH:MM:SS"	--begin=YYYY-MM-DD[THH:MM[:SS]]	-b[[year:][month:]day:]hour:minute	-a [YMMDDhhmm]	n/a